

Leading Edge • High-Performance Audio • Home Theater
Proprietary Patented Materials • Wireless Technology

CS



	CS-6R	CS-6R DVT	CS-8R	CS-6R Point	CS6-IW
Description	6.5" Coax	6.5" Dual VC	8" Coax	6.5" Coax	6.5" Dual VC
Impedance	8Ω	8Ω	8Ω	8Ω	8Ω
Tweeter	.75" Soft Dome	.75" Soft Dome	.75" Soft Dome	.75" Soft Dome	.75" Soft Dome
Woofer	6.5" Polypropylene	6.5" Polypropylene	8" Polypropylene	6.5" Polypropylene	6.5" Polypropylene
Power	5 - 100 Watts	5 - 100 Watts	5 - 120 Watts	5 - 100 Watts	5 - 100 Watts
Frequency Response	50 Hz - 20 kHz	50 Hz - 20 kHz	42 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 20 kHz
Dimensions	9.1"Dia 3.75"D	9.1"Dia 3.25"D	10.6"Dia 3.8"D	9.3"Dia 4.8"D	12.4"H 5.5"W 3.4"D
Weight	2 lbs.	2.5 lbs.	4.75 lbs.	3 lbs.	3.5 lbs.

SPACIA



	CI-MM3-II	CI1.5	CI15
Description	3" In-Wall	3" In-Ceiling	3" In-Wall
Impedance	8Ω	8Ω	8Ω
Tweeter	-	-	-
Woofer	3" Polypropylene	3" Polypropylene	3" Polypropylene
Power	5 - 60 Watts	5 - 60 Watts	5 - 60 Watts
Frequency Response	82 Hz - 22 kHz	115 Hz - 22 kHz	115 Hz - 22 kHz
Dimensions	4"H 4"W 1.9"D	6.3"DIA 3.5"D	5"H 5"W 4.125"D
Weight	1.5 lbs.	3.1 lbs.	3.1 lbs.

VELOCITY



	V52	V62	V626	V5520	V-Surround-II
Description	5.25" 2-Way	6.5" 2-Way	6.5" 3-Way Tower	5.25" 2-Way LCR	5.25" 2-Way Switchable
Impedance	8Ω	8Ω	8Ω	8Ω	8Ω
Tweeter	1" Soft Dome	1" Soft Dome	1" Soft Dome	1" Soft Dome	(2) 1" Soft Dome
Woofer	5.25" Titanium	6.5" Polypropylene	(2) 6.5" Titanium	5.25" Titanium	5.25" Titanium
Power	15 - 120 Watts	15 - 140 Watts	15 - 200 Watts	15 - 140 Watts	15 - 120 Watts
Frequency Response	55 Hz - 20 kHz	42 Hz - 20 kHz	32 Hz - 20 kHz	50 Hz - 20 kHz	60 Hz - 20 kHz
Dimensions	10.75"H 7.4"W 8.53"D	13.25"H 8.25"W 9.53"D	40.5"H 8.25"W 9.53"D	7.4"H 18"W 8.53"D	9"H 11.94"W 4.5"D
Weight	8.4 lbs.	10.5 lbs.	24 lbs.	11 lbs.	6.55 lbs

CI



	CI6.0X	CI6.1X	CI6.2X	CI7.3X	CI520	CI620	CI820	CI20X	CI60 VIII Kit	CI70X	CISURRX	CI110-SIII	CI120	CI130	CI150	IW200-II	IW210
Description	6.5" Coaxial	6.5" 2-Way	6.5" 2-Way	8" 3-Way	5.25" Coax	6.5" Coax	8" Coax	6.5" 2-Way In-Wall	6.5" 2-Way In-Wall	7" 3-Way In-Wall	6.5" 2-Way In-Wall	6.5" 2-Way In-Wall	5.25" 3-Way In-Wall	6.5" 3-Way In-Wall	5.25" 2-Way In-Wall	Dual 8" In-Wall	10" In-Wall Sub
Impedance	8Ω	8Ω	8Ω	8Ω	16Ω	16Ω	16Ω	8Ω	8Ω	8Ω	8Ω	8Ω	4Ω	4Ω	4Ω	4Ω	4Ω
Tweeter	1" Soft Dome	1" Soft Dome	.75" Soft Dome	1" Soft Dome (Midrange: 1.5" Soft Dome)	.75" Soft Dome	1" Soft Dome	1" Soft Dome	1" Soft Dome	1" Soft Dome	1" Soft Dome (Midrange: 1.5" Soft Dome)	(2) 1" Soft Dome	1" Soft Dome	1" Soft Dome (Midrange: 1.5" Soft Dome)	1" Soft Dome (Midrange: 1.5" Soft Dome)	1" Soft Dome	-	-
Woofer	6.5" Polypropylene	6.5" Woven Glass	6.5" Woven Glass	8" Woven Glass	5.25" Polypropylene	6.5" Polypropylene	8" Polypropylene	6.5" Woven Glass	6.5" Kevlar	7" Woven Glass	6.5" Woven Glass	(2) 6.5" Kevlar	(2) 5.25" Kevlar	(2) 6.5" Kevlar	(3) 5.25" Kevlar	(2) 8" Polypropylene	(2) 10" Polypropylene
Power	10 - 120 Watts	10 - 150 Watts	10 - 100 Watts	15 - 200 Watts	10 - 80 Watts	10 - 80 Watts	10 - 80 Watts	10 - 150 Watts	10 - 150 Watts	10 - 150 Watts	10 - 150 Watts	20 - 150 Watts	20 - 200 Watts	20 - 250 Watts	15 - 200 Watts	350 W Peak	350 W Peak
Frequency Response	48 Hz - 22 kHz	40 Hz - 22 kHz	45 Hz - 22 kHz	32 Hz - 22 kHz	65 Hz - 22 kHz	60 Hz - 22 kHz	55 Hz - 22 kHz	48 Hz - 20 kHz	38 Hz - 22 kHz	32 Hz - 22 kHz	45 Hz - 20 kHz	32 Hz - 22 kHz	42 Hz - 22 kHz	36 Hz - 22 kHz	55 Hz - 22 kHz	25 Hz - 160 Hz	24 Hz - 160 Hz
Dimensions	7.78"DIA 4.13"D	7.87"DIA 4.37"D	7.87"DIA 4.37"D	9.62"DIA 5"D	10.5"DIA 6"D	8.37"DIA 6"D	8.37"DIA 8.34"D	11.37"H 7.37"DIA 3.5"D	10.75"H 7.5"DIA 3.5"D	12.57"H 8.63"W 3.5"D	12.57"H 8.63"W 3.75"D	21.5"H 10"W 4"D	19.25"H 14.25"W 3.75"D	23.5"H 14"W 3.75"D	31.37"H 8.12"W 3.87"D	72"H 14.4"W 3.4"D	23.5"H 14"W 3.9"D
Weight	3 lbs.	4.5 lbs.	4.5 lbs.	6 lbs.	8 lbs.	8 lbs.	9 lbs.	5 lbs.	4.75 lbs.	5.5 lbs	5.5 lbs.	21 lbs.	20 lbs.	30 lbs.	18.5 lbs.	60 lbs.	30 lbs.

PREMIER



	PC1.5	PC33.5	PC3.5	PC9.5	PC-SURROUND-II	PC60 CA
Description	6.5" 2-Way	5.25" 3-Way LCR	6.5" 3-Way LCR	6.5" 3-Way Tower	6.5" 3-Way Switch	6.5" 2-Way
Impedance	4Ω	4Ω	4Ω	4Ω	4Ω	4Ω
Tweeter	1" Soft Dome	1" Soft Dome	1" Soft Dome	1" Soft Dome (Mid: 1.5" Soft Dome)	(2) 1" Soft Dome (Mid: 1.5" Soft Dome)	1" Soft Dome
Woofer	6.5" RPF Composite	(2) 5.25" RPF Comp.	(2) 6.5" RPF Comp.	(3) 6.5" RPF Comp.	6.5" RPF Composite	6.5" RPF Composite
Power	20 - 150 Watts	20 - 200 Watts	20 - 250 Watts	20 - 450 Watts	20 - 150 Watts	20 - 150 Watts
Frequency Response	40 Hz - 22 kHz	56 Hz - 22 kHz	36 Hz - 22 kHz	28 Hz - 22 kHz	60 Hz - 22 kHz	60 Hz - 22 kHz
Dimensions	14"H 8"W 12"D	7"H 18"W 9.6"D	22"H 8"W 12.3"D	45.5"H 9"W 14.7"D	15"H 14.5"W 5"D	13.2"H 8.6"W 8.2"D
Weight	18.14 lbs.	18.5 lbs.	32 lbs.	66 lbs.	19 lbs.	16 lbs.

HS



	HS15	HS24	HS26	HS28	HS28-LT
Description	3" Hanging	4" Coax	6.5" Coax	8" Coax	8" Coax
Impedance	8Ω	16Ω	16Ω	16Ω	16Ω
Tweeter	-	.75" Dome	.75" Dome	1" Dome	1.4" Horn Driver
Woofer	3" Polypropylene	4" Polypropylene	6.5" Polypropylene	8" Polypropylene	8" Treated Paper
Power	10 - 40 Watts	10 - 40 Watts	10 - 64 Watts	10 - 128 Watts	10 - 128 Watts
Frequency Response	120 Hz - 22 kHz	100 Hz - 22 kHz	80 Hz - 22 kHz	80 Hz - 22 kHz	80 Hz - 22 kHz
Dimensions	4.35"H	7.86"H	10.4"H	12.9"H	12.9"H
Weight	1.4 lbs.	3.9 lbs.	7 lbs.	11 lbs.	14 lbs.

TEATRO ULTRA-THIN



	TFS1.0	TCE1.5
Description	3" Dual 2-Way Surround Channel	3" 2-Way Front Channel
Impedance	8Ω	8Ω
Tweeter	.75" Soft Dome	(2) .75" Soft Dome
Woofer	(2) 3" Polypropylene	(5) 3" Polypropylene
Power	15 - 100 Watts	15 - 100 Watts
Frequency Response	65 Hz - 20 kHz	65 Hz - 20 kHz
Dimensions	6.75"H 18.5"W 1.5"D	6.75"H 26.5"W 1.5"D
Weight	5.8 lbs.	8 lbs.

TEATRO SOUNDBARS



	PC3.0	TSB3.0
Description	5.25" 3-Way LCR Soundbar	3" 2-Way Soundbar
Impedance	4Ω	8Ω
Tweeter	(3) 1" Soft Dome	(3) .75" Soft Dome
Mids/Ambient Driver	(5) 1.5" Soft Dome	(2) 1" Aluminum
Woofer	(3) 5.25" RPF Composite	(6) 3" Polypropylene
Power	15 - 150 Watts / Channel (3x)	15 - 100 Watts / Channel (3x)
Frequency Response	52 Hz - 22 kHz	75 Hz - 20 kHz
Dimensions	7"H 40"W 4.5"D	6.75"H 43"W 1.5"D
Weight	30 lbs.	15 lbs.

SUBS



	Power-FL8	Power-FL10	Power-FL12	HV101-LP	HV101-II	HV121-II	PC-Sub WL-10	PC-Sub WL-12
Description	8" Subwoofer	10" Subwoofer	12" Subwoofer	10" Subwoofer	10" Subwoofer	12" Subwoofer	10" Wireless Subwoofer	12" Wireless Subwoofer
Driver	8" Polypropylene	10" Polypropylene	12" Polypropylene	10" Treated Pulp	10" Treated Pulp	12" Treated Pulp	10" Polypropylene	12" Polypropylene
Crossover Frequency	40 - 110 Hz Variable; 24 dB/Octave + LFE	40 - 110 Hz Variable; 24 dB/Octave + LFE	40 - 110 Hz Variable; 24 dB/Octave + LFE	40 - 250 Hz Variable; 24 dB/Octave + LFE	40 - 250 Hz Variable; 24 dB/Octave + LFE	40 - 250 Hz Variable; 24 dB/Octave + LFE	35 - 120 Hz Variable; 24 dB/Octave + LFE	-35 - 120 Hz Variable; 24 dB/Octave + LFE
Crossover Type	Low Pass	Low Pass	Low Pass	Variable Low Pass	Variable Low Pass	Variable Low Pass	Low Pass	Low Pass
Max Power	250 W Cont. / 600 W Max	250 W Cont. / 600 W Max	250 W Cont. / 600 W Max	150 Watts	150 Watts	150 Watts	300 W Cont. / 900 W Max	300 W Cont. / 900 W Max
Freq Response	32 - 150 Hz	22 - 150 Hz	22 - 150 Hz	28 - 250 Hz	35 - 250 Hz	22 - 250 Hz	20 - 200 Hz	20 - 200 Hz
Dimensions	15.5"H 11.5"W 13"D	16.6"H 12.5"W 15"D	18.5"H 15"W 16.5"D	14"H 13.5"W 14.5"D	6"H 13.5"W 19.8"D	16.8"H 15.5"W 16.5"D	13"H 13.375"W 14.5"D	16" H 15" W 16.375" D
Weight	23 lbs.	30 lbs.	42 lbs.	21 lbs.	16.5 lbs.	24 lbs.	34.5 lbs.	41.5 lbs.

SOLARIS



	SPF-15	SPF-25	SPF-35	SPF-55	SPF-85	Music Garden	MG4
Description	3" Surface-Mount	5.25" Surface-Mount	6.5" Surface-Mount	5.25" Coaxial	8" Coaxial	4.4" Landscape & 1 8" In-Ground	4" Landscape
Impedance	8Ω	8Ω	8Ω	4Ω	4Ω	MG4: 8Ω	8Ω
Tweeter	-	1" Titanium Dome	1" Titanium Dome	1" Aluminum Dome	1" Aluminum Dome	MG4: .75" Titanium Dome	.75" Titanium Dome
Woofer	3" Polypropylene	5.25" Polypropylene	6.5" Polypropylene	5.25" Polypropylene	8" Polypropylene	MG4: 8" Polypropylene	4" Polypropylene
Recom. Power	5 - 40 Watts	10 - 120 Watts	10 - 150 Watts	15 - 120 Watts	15 - 200 Watts	25 - 100 Watts	25 - 100 Watts
Frequency Response	122 Hz - 22 kHz	60 Hz - 20 kHz	45 Hz - 20 kHz	49 Hz - 22 kHz	38 Hz - 22 kHz	MG4: 38 Hz - 22 kHz	85 Hz - 22 kHz
Sensitivity	85 dB	89 dB	88 dB	88 dB	88 dB	-	-
Dimensions	4.35"H 4.35"W 3.81"D	11"H 6.75"W 6.25"D	12"H 8.75"W 7.7.5"D	15.51"H 14.17"D	16.42"H 14.7"D	MG Sub: 18"H 9.75"D MG4: 17.75" H 5.625" Dia 7.8" D	17.75" H 5.63" Dia 7.8" D
Weight	1.4 lbs.	5.3 lbs.	6.8 lbs.	13 lbs.	16.7 lbs.	-	-

AMPS



	P350	P3-35
Description	P350 Class-G high current sub / full-range mono block	2/3-Channel A/V Amplifier w/ Dolby Digital® and Bluetooth® for Soundbar & TV Speakers
Power	350 W RMS @ 4Ω, 700 W peak, 225 W RMS @ 8Ω, 400 W peak	2 Channel - 50 Watts RMS/CH > 1% @ 8Ω, 55 Watts @ 4Ω 3 Channel - 35 Watts RMS/CH > 1% @ 8Ω, 40 Watts @ 4Ω
Overall Response	10 Hz - 20 kHz +/- 25 dB	10 Hz - 20 kHz @ 1W RMS 8Ω > .1% THD ±5 dB
Frequency Response	10 Hz - 20 kHz	10 Hz - 20 kHz @ 1 Watt RMS 8Ω > .1% THD
Dimensions	2" H 17.25" W 13.25" D	2" H 17.25" W 13.25" D
Weight	17 lbs.	1 lbs.