

Rockustics®

ULTRA-FIDELITY OUTDOOR SPEAKERS™

Handcrafted in the USA • Fully Weatherproof • Fade & Chip Resistant
Custom Styles • High-Fidelity Audio

ROCK SERIES



	PunkRock	Rocky III	EconoRock	Rocquette	Pavarocci	OctoRock	Rocky Jr.	StoneHenge II	SubSub 10	SubSub 12	SubSub 15
Description	5.25" Coax	6.5" Coax	6.5" Coax	6.5" Coax	8" Coax	8" Coax	6.5" 2-Way	8" 2-Way	10" In-Ground Sub	12" In-Ground Sub	15" In-Ground Sub
Impedance	4Ω	4Ω	4Ω	4Ω	4Ω	4Ω	8Ω	4Ω	8Ω	8Ω	8Ω
Tweeter	.75" Dome	.75" Dome	.75" Dome	.75" Dome	.75" Dome	.75" Dome	1" Dome	1" Dome	-	-	-
Woofers	5.25" Polypropylene	6.5" Polypropylene	6.5" Polypropylene	6.5" Polypropylene	8" Polypropylene	8" Polypropylene	6.5" Polypropylene	8" Polypropylene	10" Polypropylene	12" Polypropylene	15" Polypropylene
Power	75 Watts	70 Watts	70 Watts	70 Watts	70 Watts	100 Watts	100 Watts	150 Watts	250 Watts	300 Watts	350 Watts
Freq. Response	76 Hz - 19.5 kHz	62 Hz - 20 kHz	65 Hz - 20 kHz	60 Hz - 20 kHz	62 Hz - 20 kHz	55 Hz - 20 kHz	69 Hz - 19 kHz	70 Hz - 19 kHz	32 - 105 Hz (-3 dB)	27 - 110 Hz (-3 dB)	29 - 117 Hz (-3 dB)
Dims	8.3"H 10.5"W 9.5"D	10.5"H 13"W 13"D	11"H 12.5"W 11"D	9"H 15.5"W 11"D	13"H 16"W 13.5"D	13"H 16"W 12.5"D	16"H 20"W 10.5"D	18"H 17"W 14.5"D	18"H 17"W 14.5"D	25"H 13.8"W 26"D	31"H 19"W 39"D
Weight	11 lbs.	14 lbs.	15 lbs.	16 lbs.	24 lbs.	32 lbs.	34 lbs.	45 lbs.	23 lbs	28 lbs	126 lbs.

OMNI SERIES



	OmniPlanter 5.25	OmniPlanter 6.5	OmniPlanter 8.0	SurroundStone 5	SurroundStone 8
Description	5.25" Coax Planter	6.5" Coax Planter	8.0" Coax Planter	5.25" Coax Omnidirectional	8" Coax Omnidirectional
Impedance	4Ω	4Ω	4Ω	4Ω	4Ω
Tweeter	.75" Dome	.75" Dome	.75" Dome	.75" Dome	.75" Dome
Woofers	5.25" Polypropylene	6.5" Polypropylene	8" Polypropylene	5.25" Polypropylene	8" Polypropylene
Power	70 Watts	70 Watts	75 Watts	75 Watts	100 Watts
Freq. Response	65 Hz - 19 kHz	65 Hz - 20 kHz	55 Hz - 20 kHz	60 Hz - 20 kHz	50 Hz - 20 kHz
Dims	16"Dia 14"H	20"Dia 18"H	24"Dia 20"H	9"H 15.5"W 11"D	13"H 16"W 13.5"D
Weight	12 lbs.	14 lbs.	20 lbs.	40 lbs.	45 lbs.

SWEETSPOT SERIES



	Rocquette SweetSpot	Pavarocci SweetSpot	OmniPlanter 6.5 SweetSpot	OmniPlanter 8.0 SweetSpot	PunkSub
Description	6.5" Single-Point Stereo	8" Single-Point Stereo	6.5" Single-Point Stereo	8" Single-Point Stereo	Dual 8" Subwoofer
Impedance	4Ω	4Ω	4Ω	4Ω	4Ω
Tweeter	(2) .75" Dome	(2) .75" Dome	(2) .75" Dome	(2) .75" Dome	-
Woofers	6.5" Dual VC	8" Dual VC	6.5" Dual VC	8" Dual VC	(2) 8" Polypropylene
Power	70 Watts	100 Watts	70 Watts	75 Watts	200 W
Freq. Response	60 Hz - 20 kHz	62 Hz - 20 kHz	65 Hz - 20 kHz	55 Hz - 20 kHz	45 - 100 Hz
Dims	9"H 15.5"W 11"D	13"H 16"W 13.5"D	20"Dia 18"H	24"Dia 20"H	11.5"H 21"W 18"D
Weight	16 lbs.	24 lbs.	14 lbs.	20 lbs.	85 lbs.

ESCAPE SERIES



	MusicGarden	Periscope 4	Periscope 6	Subscape 8	Subscape 10	Subscape 12
Description	(4) 4" Landscape (1) 8" Titanium Dome	4" Landscape	6.5" Landscape	8" In-Ground Sub	10" In-Ground Sub	12" In-Ground Sub
Impedance	8Ω	8Ω	8Ω	8Ω	8Ω	8Ω
Tweeter	MG4: .75" Titanium Dome	.75" Titanium Dome	1" Titanium Dome	-	-	-
Woofers	MG Sub: 8" Polypropylene MG4: 4" Polypropylene	4" Polypropylene	6.5" Polypropylene	8" Polypropylene	10" Polypropylene	12" Polypropylene
Power	25 - 100 Watts	50 Watts	100 Watts	150 Watts	250 Watts	300 Watts
Freq. Response	MG4: 38 Hz - 22 kHz	85 Hz - 22 kHz	65 Hz - 22 kHz	38 - 135 Hz (-3 dB)	32 - 105 Hz (-3 dB)	27 - 110 Hz (-3 dB)
Dims	MG Sub: 18"H 9.75"D MG4: 17.75"H 5.625"Dia 7.8"D	5.7"Di 18" H 7.5"D	8.7"Di 21"H 10.3"D	28.5"H 9.75"D	25"H 12"W 25"D	25"H 13.75"W 26"D
Weight	MG Sub: 13.5 lbs MG4: 4.5 lbs.	4.5 lbs.	7.5 lbs.	13.5 lbs.	23 lbs.	28 lbs.

AMPS



	P350	MA3501t	OS-440	P3-35
Description	P350 Class-G high current sub / full-range mono block	Efficient Class-G high current mono block 350 W	4-Channel, weatherproof, wifi streaming with smart device	3 channel, Bluetooth enabled, IR learning, line-level subwoofer out
Power	350 W RMS @ 4Ω, 700 W peak, 225 W RMS @ 8Ω, 400 W peak	350 W RMS @ 4Ω, 700 W peak, 225 W RMS @ 8Ω, 400 W peak HP Filter-Switchable: 40 - 60 Hz	4 x 40 watts >1% @ 4 - 8 ohm 2 x 80 watts >1% @ 8 ohm	2 Channel - 50 watts RMS/CH >1% @ 8 ohms, 55 watts @ 4 ohms; 3 Channel - 35 watts RMS/CH >1% @ 8 ohms, 40 watts @ 4 ohms
Overall Response	10 Hz - 20 kHz +/- 25 dB	20 - 100 Hz ± 3 dB direct, 30 Hz - 35 kHz ± .5 dB	0Hz - 20 kHz @ 1 Watt RMS 8 ohms >.1% THD	0 Hz - 20 kHz @ 1 Watt RMS 8 ohms >.1% THD
Dimensions	2" H 17.25" W 13.25" D	3.5" H 13.75" W		1.25" H 3.9" W 7.25" D



ROCKUSTICS® ROCK AND PLANTER SPEAKERS ARE HANDCRAFTED IN LENEXA, KANSAS