

Sound from any Surface • Smooth, Even Coverage • Connects Like a Speaker
Sound Masking • Designed to Last

MODELS



SD1



SD1g



SD1sm



SD1 Desktop Kit 250



MSK-1



MSK-1g



MSK-1sm

Description	Attaches to drywall and similar surfaces with our patented cantilever spring mounting bracket (sold separately). Designed for one channel of audio. Optional EQ module optimizes the SD1 for use on drywall.	Attaches to glass and other non-porous surfaces using double-sided adhesive disk (included). Designed for one channel of audio. Optional EQ module optimizes the SD1 for use on glass.	Attaches to wood and similar surfaces using wood screws (included). Designed for one channel of audio. Optional EQ module optimizes the SD1 for use on wood surfaces.	Portable SD1 kit for use on top of horizontal surfaces. Includes: one (1) SD1 desktop unit, DC power adapter, cables and SD-250 mini amp with SolidDrive EQ curves in a convenient carrying case.	Attaches to drywall and similar surfaces with our patented cantilever spring mounting bracket (sold separately). Designed for one channel of sound masking audio.	Attaches to glass and other non-porous surfaces using double-sided adhesive disk (included). Designed for one channel of sound masking audio.	Attaches to wood and similar surfaces using wood screws (included). Designed for one channel of sound masking audio.
Nominal Impedance	8Ω	8Ω	8Ω	8Ω	8Ω	8Ω	
Frequency Response	60 Hz - 15 kHz Nominal w/o EQ	60 Hz - 15 kHz Nominal w/o EQ	60 Hz - 15 kHz Nominal w/o EQ	60 Hz - 15 kHz Nominal w/o EQ	70 Hz - 15 kHz Nominal w/o EQ	70 Hz - 15 kHz Nominal w/o EQ	
Max Program Power	100 Watts, with 100 Hz 12 dB / Octave High Pass	100 Watts, with 100 Hz 12 dB / Octave High Pass	100 Watts, with 100 Hz 12 dB / Octave High Pass	100 Watts, with 100 Hz 12 dB / Octave High Pass	50 Watts, with 100 Hz 12 dB / Octave High Pass	50 Watts, with 100 Hz 12 dB / Octave High Pass	
Max Continuous Power	30 Watts	30 Watts	30 Watts	30 Watts	30 Watts	30 Watts	
Housing Body Dimensions	Diameter: 58.6 mm (2.3") Height: 52.34 mm (2.06")	Diameter: 58.6 mm (2.3") Height: 52.34 mm (2.06")	Diameter: 58.6 mm (2.3") Height: 52.34 mm (2.06")	Diameter: 58.6 mm (2.3") Height: 52.34 mm (2.06")	Diameter: 58.6 mm (2.3") Height: 52.34 mm (2.06")	Diameter: 58.6 mm (2.3") Height: 52.34 mm (2.06")	
Mounting Foot Diameter	89 mm (3.5")	51 mm (2.05")	89 mm (3.5")	51 mm (2.05")	89 mm (3.5")	51 mm (2.05")	
Coverage	120°	120°	120°	120°	120°	120°	
Colors	Titanium	Chrome, Titanium, Adonized Black	Chrome, Titanium, Adonized Black	Adonized Black	Titanium	Titanium	
UL Approved	1480 & 2043	1480 & 2043	1480 & 2043	N/A	1480 & 2043	1480 & 2043	

MODELS



MSK-1-T



MSK-1g-T



MSK-1sm-T

Description	Attaches to drywall and similar surfaces with the patented cantilever spring mounting bracket (sold separately). 10 Watt, multi-tap transformer built in. Designed for one channel of sound masking audio.	Attaches to glass and other non-porous surfaces using double-sided adhesive disk (included). 10 Watt, multi-tap transformer built in. Designed for one channel of sound masking audio.	Attaches to wood and similar surfaces using wood screws (included). 10 Watt, multi-tap transformer built in. Designed for one channel of sound masking audio.
Frequency Response	80 Hz - 15 kHz Nominal w/o EQ	80 Hz - 15 kHz Nominal w/o EQ	80 Hz - 15 kHz Nominal w/o EQ
Max Transformer Power	10 Watts	10 Watts	10 Watts
Housing Body Dimensions	Diameter: 58.6 mm (2.3") Height: 120.7 mm (4.75")	Diameter: 58.6 mm (2.3") Height: 120.7 mm (4.75")	Diameter: 58.6 mm (2.3") Height: 120.7 mm (4.75")
Mounting Foot Diameter	89 mm (3.5")	51 mm (2.05")	89 mm (3.5")
Coverage	120°	120°	120°
Colors	Titanium	Titanium	Titanium
UL Approved	1480 & 2043	1480 & 2043	1480 & 2043

IN-WALL



IW200-Kit



IW210

Description	In-wall subwoofer designed to mount in walls and between wall studs. Includes separate sealed back box. It is designed for use with the P350 subwoofer amplifier.	In-wall subwoofer with sealed enclosure designed to mount flush in walls and between wall studs. Easily retrofittable into existing walls. It is designed for use with the P350 subwoofer amplifier.
Woofer	Dual 8" Mica-Graphite Polypropylene	Dual 10" Mica-Graphite Polypropylene Woofer and Bass Radiator
Frequency Response	25 - 160 Hz	24 - 160 Hz
Impedance	4Ω	8Ω
Enclosure	Sealed	Sealed
Enclosure Dimensions	Height: 1828.8 mm (72") Width: 375.76 mm (14.4") Depth: 86.35 mm (3.4")	Height: 596.9 mm (23.5") Width: 355.6 mm (14") Depth: 99.06 mm (3.9")
Cutout Dimensions	520.7 mm (20.5") H x 222.25 mm (8.75") W	568.325 mm (22.375") H x 330.2 mm (13") W
Weight	27.2 kg (60 lbs) Subwoofer and back box	13.6 kg (30 lbs)
Grille	White Powder-Coated Galvanized Magnetic Micro-Flange	White Powder-Coated Galvanized Magnetic Micro-Flange

AMPS



SA202-RDT/SA202



SD-250



P350

Description	Compact 2-channel amplifier with extra heat sink surfaces for extended duty at full power. Rated at 20 Watts per channel. Dual RCA, stereo mini jack and high-level inputs. Power inputs include either three-pin euroblock or barrel connector, 12-volt trigger for automatic on/off functions when source power is detected.	Compact 2-channel amplifier with extra heat sink surfaces for extended duty at full power. Rated at 50 Watts per channel. Stereo, mono or bridged mono. Balanced stereo euroblock, stereo unbalanced mini jack, or high-level euroblock inputs.	Class-G high current 350 Watt amplifier for use as a subwoofer or full range mono-block amp. Rack mountable.
Frequency Response	20 Hz - 20 kHz	20 Hz - 20 kHz	10 Hz - 20 kHz
Input Impedance	6K Ω	47K Ω	22K Ω Unbalanced 37.5K Ω Balanced
Max Gain	35 dB	34 dB	
Dimensions	Height: 31.2 mm (1.23") Width: 101.1 mm (3.98") Depth: 123.6 mm (4.86")	Height: 31.2 mm (1.23") Width: 101.1 mm (3.98") Depth: 123.6 mm (4.86")	Height: 53.34 mm (2.1") Width: 482.6 mm (19.0") Depth: 336.55 mm (13.25")
Weight	0.25 kg (0.55 lbs) - amp only 0.59 kg (1.3 lb) - with amp and power supply (SA202-RDT)	0.26 kg (0.56 lbs) - amp only	Height: 44.45 mm (1.75") Width: 438.2 mm (17.25") Depth: 336.55 mm (13.25")
Optional Accessories	AC-SA202-RMA (Rack Mount Adapter)	AC-SA502-RMA (Rack Mount Adapter)	7.71 kg (17 lbs)

ACCESSORIES



Mounting Bracket



Passive EQ Modules



Color Options



Heat Sink Fins